

EX330 – Multimedia Projector

Bold, Bright and Brilliant

The EX330 is an ultra-portable, XGA digital projector from Optoma for the road warrior. Ideal for “grab and go” presentations, the Optoma EX330 is unparalleled in size, weight and connections. It also features BrilliantColor™ technology and a DLP® chipset from Texas Instruments for crisp and amazing picture quality.

Features

- Ultra portable 2.4-lb DLP projector
- Native XGA resolution and HD compatible
- 2200 ANSI lumens and 2000:1 contrast ratio
- Connections include HDMI, VGA, s-video, composite video and USB
- Ideal presentation remote with laser pointer and page-advance features
- Up to 5000 hours lamp life

Specifications

Display Technology
Single 0.55” DMD DLP
Technology by Texas Instruments

Resolution
Native XGA (1024 x 768)

Maximum Resolution
SXGA+ (1400 x 1050)

Brightness (Typical)
2200 ANSI Lumens

Contrast Ratio
2000:1 (Full On/Full Off)

Lamp Life and Type
5000/3000 Hours (STD/Bright)
165W P-VIP

Throw Ratio
1.95 to 2.15:1 (Distance/Width)

Image Size (Diagonal)
22.9” to 302” (0.58 to 7.67m)

Projection Distance
3.3’ to 39.37’ (1.0 to 12m)

Remote Control
Fully Featured Remote Control
w/Mouse and Laser Pointer

Displayable Colors
16.7 Million

Aspect Ratio
4:3 Native, 16:9 Compatible

Uniformity
85%

Offset
115%

Computer Compatibility
VGA, SVGA, XGA, SXGA,
SXGA+, WXGA Resized, VESA,
PC and Macintosh Compatible

Video Compatibility
NTSC, PAL, SECAM, SDTV
(480i), EDTV (480p), HDTV
(576i/p, 720p, 1080i)

User Controls
Complete On-Screen Menu
Adjustments in 22 Languages

Keystone Correction
± 18° Vertical

Horizontal Scan Rate
15 to 100 kHz

Vertical Refresh Rate
43 to 85 Hz

Projection Lens
F=2.41~2.55, f=21.79~23.99mm,
1.10x Manual Zoom and Focus

I/O Connectors
HDMI, VGA-In, Composite
Video, S-Video, USB

Security
Kensington® Lock Port

Projection Method
Front, Rear, Ceiling Mount,
Table Top

Weight
2.4 lbs (1.1 kg)

Dimensions (W x H x D)
8” x 2.5” x 6.1”
(205.5 x 64 x 156 mm)



Noise Level (STD/Bright)
31dB/33dB

Power Supply
AC Input 100-240V,
Auto-Switching

Power Consumption
225 Watts (Maximum),
<1 Watts (Standby)

Operating Temperature
41 - 104°F (5 - 40°C) (80%
Humidity), Adjustable Fan Speed
for High Altitude Application

Standard Accessories
AC Power Cord, VGA to VGA
Cable, USB Cable, Carrying
Case, Remote Control, Batteries
for Remote, Quick Start Guide,
Warranty Card and User’s
Manual

Optional Accessories
Ceiling Mount, S-Video Cable,
VGA to Component Cable,
Composite Video Cable, DVI to
HDMI Adapter, HDMI Cable,
Gold Service Warranty and
Panoview™ Series Screens

Warranty
2 Years Limited Parts and Labor,
90 Days on Lamp

UPC
796435 11 689 7

Accessory Part Numbers
Lamp: BL-FP165A
Remote: BR-5021L
Case: BK-4022