

EX615 – Multimedia Projector

Bright, Network-Ready Projector

The Optoma EX615 delivers outstanding image quality and features wired and wireless capabilities – ideal for both install and portable applications. Featuring RJ45 connection for remote network monitoring and control, the EX615 is also upgradable with an optional wireless dongle that simplifies connection. Best-in-class to deliver exceptional brightness required in large conference rooms, meeting rooms, training facilities and classrooms. The EX615 is designed for low cost of ownership with filter-free design, long lamp life and low power consumption.



Features

- Easy-to-read text – bright at 3500 ANSI lumens and high 3000:1 contrast ratio
- VGA and audio pass-thru operational on standby mode
- Remote management via RS-232 or RJ45 connectivity
- Broad range of audio and video connectivity
- Wireless connectivity with optional dongle



Specifications

Display Technology

Single 0.55" DMD DLP Technology by Texas Instruments

Resolution

Native XGA (1024x768)

Maximum Resolution

UXGA (1600x1200)

Brightness (Typical)

3500 ANSI Lumens

Contrast Ratio

3000:1 (Full On/Full Off)

Lamp Life and Type

4000/3000 Hours (STD/Bright)
230W P-VIP

Throw Ratio

1.95 to 2.15:1 (Distance/Width)

Projection Distance

3.93' to 39.3' (1.2 to 12m)

Image Size (Diagonal)

27.5" to 303" (0.7 to 7.69m)

Aspect Ratio

4:3 Native, 16:9 and 16:10
Compatible

Audio

Two 5-Watt Stereo Speakers

Remote Control

Fully Featured IR Remote with Laser Pointer and Mouse Functions

Displayable Colors

1.07 Billion

Offset

115%

Uniformity

85%

Computer Compatibility

UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)

Keystone Correction

±40° Vertical

Horizontal Scan Rate

15.3 to 91.1 KHz

Vertical Refresh Rate

25 to 85 Hz

Loop Through

Monitor: D-Sub 15-Pin VGA Output
Audio: Stereo Mini-Jack Output (Functional in Both Normal and Standby Modes)

Projection Lens

F= 2.4-2.55, f= 21.8-24mm,
1.1x Manual Zoom and Focus

User Controls

Complete On-Screen Menu
Adjustments in 23 Languages

I/O Connectors

HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-Out, 12v trigger, RJ45, RS-232 and USB

Security

Keypad Lock, Kensington® Lock and Security Bar

Projection Method

Front, Rear, Ceiling Mount, Table Top

Weight

6.4 lbs (2.9kg)

Dimensions (W x H x D)

12.76" x 3.82" x 9.21"
(324 x 97 x 234 mm)

Noise Level (STD/Bright)

29dB/31dB

Operating Temperature

41 to 104°F (5 to 40°C),
80% Max Humidity

Power Supply

AC Input 100-240V, 50-60Hz,
Auto-Switching

Power Consumption

328 Watts (Bright), 272 Watts (STD) <1 Watt (Standby)

Warranty

One Year Limited Parts and Labor,
90 Days on Lamp

Standard Accessories

AC Power Cord, VGA to VGA Cable, USB Cable, Remote Control, Batteries for Remote, Carrying Case, Lens Cap, CD-ROM User's Manual, Quick Start Card and Warranty Card

Optional Accessories

Ceiling Mount, Wireless Dongle, HDMI Cable, VGA to Component Cable, S-Video Cable, Composite Video Cable, RS-232 Cable and Panoview™ Series Screens

UPC

796435 41 190 9

Accessory Part Numbers

Lamp: BL-FP230D
Remote: BR-5030L
Mount: BM-5001U
Case: BK-4028
Wireless Dongle: BI-EXTGB