

# 3D HOME THEATER PROJECTOR HD90



## LED DIGITAL HOME CINEMA PROJECTOR







1200 lumens bright with a stunning 500,000:1 contrast ratio with Dynamic black for deeper blacks with exceptional shadow detail

All glass multi-coated lens with vertical and horizontal lens shift provides superior focus and installation flexibility

VESA 3D Sync Port with 2D to 3D conversion. Enjoy your favorite movie or TV show in full 3D

ISF calibration settings for Day/Night viewing modes
Enjoy super wide 2.35:1 content, Auto235 feature

supports fixed and powered anamorphic lenses



1080p







The Optoma HD90 is a top of the line full LED, home cinema projector. It's a product of Optoma's 10+ years of experience in projector design for home theater.

Its LED light source delivers 1200 lumens bright images with a mind-blowing 500,000:1 contrast ratio. Produces 127% wider color gamut than similar lamp based projectors, the result is a fantastic image quality with deep vibrant colors and superb saturation.

The Optoma HD90 is packed with an extensive list of advanced features. PureMotion technology for sharp, fluid, judder free video, UltraDetail technology further enhances visible detail, Full 3D capability with 2D to 3D conversion. The projector analyzes every frame to generate a natural 3D effect from 2D sources. Vertical and horizontal lens shift combined with a razor sharp 1.9x zoom ratio projection lens for maximum installation flexibility, ultra-quiet operation and much more.

Optoma's commitment to quality ensures your projector will provide years of care-free operation.

**CONNECTIVITY** (May require optional accessories)



DLP

















Roku®

Apple TV®

### **3D HOME THEATER PROJECTOR** — HD90

### **OPTICAL/TECHNICAL SPECIFICATIONS**

Display Technology	Single 0.65" DC3 DMD DLP® Technology by Texas Instruments™
Native Resolution	HD (1920 x 1080)
Maximum Resolution	WUXGA (1920 x 1200)
Brightness	1200 lumens
Contrast Ratio	500,000:1 (full on/full off)
Displayable Colors	1.07 Billion
Lamp Life and Type	20,000+ hours LED
Projection Method	Front, rear, ceiling mount, table top
Keystone Correction	±15°
Uniformity	>85%
Offset	±60% Vertical, ±10% Horizontal
Aspect Ratio	16:9 Native, 4:3 compatible
Throw Ratio	1.22-1.52 (distance/width)
Projection Distance	3.5'-55.2'
Image Size	40"-500"
Projection Lens	F=2.0-2.32, f=18.07-22.59, 1.25x Zoom & Focus
Noise Level	23dB
Remote Control	IR backlit remote control
Operating Room Temperature	41-104°F (5-40°C), 85% max humidity
Power Supply	AC Input 100–240V, 50–60Hz, auto-switching
Power Consumption	Max 225 Watts, Min 120 Watts, <0.5W (standby-ECO)

## **COMPATIBILITY SPECIFICATIONS**

Computer Compatibility	WUXGA, HD, UXGA, SXGA+, WXGA, SXGA, XGA, SVGA, VGA
Video Input Compatibility	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
3D Compatibility	Supports all HDMI 1.4a mandatory 3D formats (Frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz (i.e 60 or 72 frames per eye). 3D glasses are needed and is sold separately. Refer to user manual for details.
Vertical Scan Rate	24–85Hz, 120Hz
Horizontal Scan Rate	15.375–91.146KHz
User Controls	Complete on-screen menu adjustment in 22 languages
I/O Connection Ports	Two HDMI 1.4a, VGA-in, component, composite video, USB-A (charging port), RS-232C, two 12V triggers, 3D VESA port

## PHYSICAL SPECIFICATIONS

Security	Kensington® lock port, and keypad lock
Weight	15.4 lb (7 kg)
Dimensions (W x H x D)	13.6" x 6.4" x 17.4" (345 x 161.5 x 443 mm)



#### Warrant

3-Year Optoma Express Service

## In the Box (Standard Accessories)

HD90 projector, AC power cord, remote control, batteries for remote, RF 3D glasses, RF 3D emitter, multilingual CD-ROM user's manual, quick start card, and warranty card

## **Optional Accessories**

HDMI cable, ceiling mount, Optoma screen, RF 3D glasses, RF 3D emitter

## **Accessory Part Numbers**

Power Cord (11M): BC-PUPIXY11 VGA to component adaptor: BC-VGCRXY00 RF 3D Glasses: ZF2300GLASSES

Mount: BM-5001U RF 3D emitter: BC300 Remote: SP.85F02GC01

UPC 796435 81 199 0



