

# TH1060P – HD 1080p Projector

## Fully Loaded High-Definition

The Optoma TH1060P, a native 1080p high-definition DLP projector, delivers clear widescreen images to ensure that your audience experiences the full impact of your message. Bright enough for use in large conference rooms and classrooms, the Optoma TH1060P includes a wide range of analog and digital connectivity options for your high-resolution sources. With the Crestron RoomView® user-friendly interface, you can easily monitor, manage and control the Optoma TH1060P remotely via RJ45 connectivity.

## Features

- HD Native (1920X1080) DLP® by Texas Instruments with BrilliantColor™ Technology
- Bright images and high contrast ratio – 4500 ANSI lumens and 2500:1 contrast ratio (full on/full off)
- Presentation-friendly IR remote with USB mouse function and laser pointer
- Crestron RoomView® for projector management and control via RJ45 connection
- Environment-friendly – consumes <1 watt of power in standby mode
- Includes closed captioning

## Specifications

### Display Technology

Single 0.65" DC2 DMD Chip DLP Technology by Texas Instruments

### Native Resolution

HD (1920 x 1080)

### Brightness (Typical)

4500 ANSI Lumens

### Contrast Ratio

2500:1 (Full On/Full Off)

### Lamp Life and Type\*

3000/2000 Hours (STD/Bright)  
300W P-VIP

### Throw Ratio

1.59 to 1.91:1 (Distance/Width)

### Projection Distance

3.28' to 32.8' (1.0 to 10m)

### Image Size (Diagonal)

23.6" to 300" (0.6 to 7.62m)

### Offset

115%

### Displayable Colors

1.07 Billion

### Uniformity

85%

### Audio

3-Watt Speaker

### Noise Level (STD/BRIGHT)

28dB/30dB

### Remote Control

IR Remote Mouse Control

### User Controls

Complete On-Screen Menu Adjustments in 23 Languages

### Computer Compatibility

HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

### Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)

### Monitor Loop Through

D-Sub 15-Pin VGA Output (Functional in Both Normal and Standby Modes)

### Projection Lens

F=2.5-2.76, f=23.5-28.2mm, 1.2x Manual Zoom and Focus

### I/O Connectors

Two HDMI, VGA-In, VGA-Out, Component, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-In, Stereo Audio-Out, RS-232, USB, RJ45 and 12V trigger.

### Security

Kensington® Lock Port and Keypad Lock

### Projection Method

Front, Rear, Ceiling Mount, Table Top

### Weight

7.8 lbs (3.53kg)

### Dimensions (W x H x D)

12.8" x 4.29" x 10.19"  
(326 x 109 x 259 mm)

### Keystone Correction

±15° Vertical



### Horizontal Scan Rate

15, 31 - 90 KHz

### Vertical Refresh Rate

50 - 85 Hz

### Operating Temperature

41 to 104°F (5 to 40°C), 85% Max Humidity

### Power Supply

AC Input 100-240V, 50-60Hz, Auto-Switching

### Power Consumption

380 Watts (Bright), 320 Watts (STD), <1 Watt (Standby)

### Standard Accessories

AC Power Cord, VGA to VGA Cable, Remote Control, Batteries for Remote, Carrying Case, Lens Cap, Multilingual CD-ROM User's Manual, Quick Start Card and Warranty Card

### Optional Accessories

HDMI Cable, Ceiling Mount, VGA to Component Cable, S-Video Cable, Composite Video Cable, RS-232 Cable and Panoview™ Series Screens

### Warranty

3-Year Optoma Express Replacement Service, 1-Year on Lamp

### UPC

796435 41 719 2

### Accessory Part Numbers

Lamp: BL-FS300C

Mount: BM-5001U

Remote: BR-5033L

Case: BK-4013

\* Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.