

**PRESENTATION PROJECTORS**

**3-Year Express Warranty**

Model	MAP	3D	Weight / Dimensions (WxHxD)	ANSI Lumens	Contrast (Full On/Off)	Native Resolution	Lamp Life (STD/Bright)	Throw Ratio	Image Size (Diagonal)	Projection Lens	Speaker	Inputs/Outputs	Comm and Control	Wired/Wireless Presentation
<b>PORTABLE - ULTRA</b>														
<a href="#">TX330</a>	\$799	—	2.4 lb 8" x 2.5" x 6.1"	2200	2000:1	1024 x 768	5000/3000	1.95–2.15	22.9"–302"	Manual Zoom and Focus	—	HDMI, VGA, S-Video, Composite Video, USB	—	—
<a href="#">TW330</a>	\$899	—		2200	2000:1	1280 x 800	5000/3000	1.55–1.7	27.3"–359"					
<a href="#">TX7156</a>	\$849	—	3.2 lb 8.7" x 2.8" x 7.0"	3000	2500:1	1024 x 768	3000/2000	1.8–2.2	26.9"–311"	Manual Zoom and Focus	1-Watt Speaker	HDMI, VGA-In, S-Video, Composite Video, Stereo Audio-In, USB	—	—
<a href="#">TW1692</a>	\$949	—		3000	2500:1	1280 x 800	3000/2000	1.5–1.76	30.9"–371"					
<a href="#">W304M*</a>	\$849	<b>Full 3D</b>	3.3 lb 8.7" x 2.8" x 7.0"	3100	10,000:1	1280 x 800	5000/4000	1.5–1.76	30.9"–371.4"	Manual Zoom and Focus	1-Watt Speaker	HDMI v1.4a, VGA-In, Composite Video, Audio-In/Out, USB-B	—	—
<b>PORTABLE - ENTRY</b>														
<a href="#">DX339**</a>	No MAP		5 lb 11.3" x 3.5" x 9.3"	2600	5000:1	1024 x 768	6500/4500	1.95–2.15	22.9"–300"	Manual Zoom and Focus	2-Watt Speaker	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Audio-In, Audio-Out, USB-B	RS-232	—
<a href="#">DW339**</a>	No MAP		5 lb 11.3" x 3.5" x 9.3"	2600	5000:1	1280 x 800		1.55–1.7	27.2"–301"					
<a href="#">DS325**</a>	No MAP		5 lb 11.3" x 3.9" x 7.6"	2800	10,000:1	800 x 600	6500/4500	1.9–2.17	22.9"–300"	Manual Zoom and Focus	—	VGA-in, S-video, composite video, RS-232	—	—
<a href="#">TS551</a>	\$429		4.9 lb 11" x 3.0" x 9.0"	2800	3500:1	800 x 600	6000/5000	1.97–2.17	30"–300"	Manual Zoom and Focus	2-Watt Speaker	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Audio-In, Stereo Audio-In/Out, USB Type B	RS-232	—
<a href="#">TX551</a>	\$479			2800	3500:1	1024 x 768								
<a href="#">DW312**</a>	\$599		5 lb 11.3" x 4.0" x 7.6"	3200	3000:1	1280 x 800	6000/3000	1.55–1.7	27.2"–301"	Manual Zoom and Focus	2-Watt Speaker	HDMI, VGA-In, VGA-Out, S-Video, Composite Video, Stereo Audio-In/Out	RS-232	—



TW775



DW312



W304M



TX779P-3D

\*W304M is subject to the 2-Year Express Warranty. \*\*D series, ML series, Home series, and Pico projectors have 1-Year Warranty.

**PRESENTATION PROJECTORS (continued)**



**3-Year Express Warranty**

Model	MAP	3D	Weight / Dimensions (WxHxD)	ANSI Lumens	Contrast (Full On/Off)	Native Resolution	Lamp Life (STD/Bright)	Throw Ratio	Image Size (Diagonal)	Projection Lens	Speaker	Inputs/Outputs	Comm and Control	Wired/Wireless Presentation
<b>PORTABLE - CONFERENCE</b>														
<a href="#">TX631-3D</a>	\$599		4.9 lbs 11" x 3.08" x 9.06"	3500	10,000:1	1024 x 768	6000/3500	1.97–2.17	30"–300"	Manual Zoom and Focus	7-Watt Speaker	HDMI, Two VGA-In, VGA-Out, Composite Video, Audio-In/Out, mini-USB, S-Video	RS-232, RJ45	Wireless via optional VGA dongle
<a href="#">TW631-3D</a>	\$699			3500	10,000:1	1280 x 800		1.47–1.81						
<a href="#">TX635-3D</a>	\$699		4.4 lbs 11.3" x 3.0" x 8.6"	3500	10,000:1	1024 x 768	6000/3000	1.6–1.92	30"–307"	Manual Zoom and Focus	10-Watt Speaker	HDMI, Two VGA-In, VGA-Out, Composite Video, Two Audio-In, Audio-Out, Mic-In, USB Type B for mouse, USB Type A for wireless or thumb drive, mini-USB Type B for display, S-Video	RS-232, RJ45	Wired and wireless (optional USB dongle)
<a href="#">TW635-3D</a>	\$799			3500	10,000:1	1280 x 800		1.28–1.536						
<a href="#">TX762</a>	\$999		6.4 lb 12.76" x 3.82" x 9.21"	4000	3000:1	1024 x 768	3000/2000	1.6–1.92	30"–307"	Manual Zoom and Focus	8-Watt Speaker	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-out, USB, 12V Trigger	RS-232, RJ45	Wireless via optional VGA dongle
<a href="#">TW762</a>	\$1,099			4000	3000:1	1280 x 800		4000/3000						
<a href="#">TX779P-3D</a>	\$1,599		7.8 lb 12.8" x 4.29" x 10.19"	5000	3000:1	1024 x 768	3000/2000	1.8–2.1	23.4"–300"	Manual Zoom and Focus	3-Watt Speaker	HDMI, Two VGA-In, VGA-Out, DVI-D, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-In/Out, USB, 12V Trigger	RS-232, RJ45	—
<b>1080p DATA</b>														
<a href="#">TH1020</a>	\$1,099	—	6.4 lb 12.76" x 3.82" x 9.21"	3000	2200:1	1920 x 1080	4000/3000	1.5–1.8	37.6"–301.1"	Manual Zoom and Focus	8-Watt Speaker	HDMI, VGA-In, VGA-Out, S-Video, Composite Video Stereo RCA Audio -in, Stereo Audio-In/Out, USB, 12V Trigger	RS-232	—
<a href="#">TH1060P</a>	\$1,499	—	7.8 lb 12.8" x 4.29" x 10.19"	4500	2500:1	1920 x 1080	3000/2000	1.59–1.91	23.6"–300"	Manual Zoom and Focus	3-Watt Speaker	Two HDMI, VGA-In, VGA-Out, Component, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-In/Out, USB, 12V Trigger	RS-232, RJ45	—
<b>INTEGRATED WIRELESS</b>														
<a href="#">TX765W<sup>§</sup></a>	\$1,499	—	12 lb 14.3" x 5" x 11.1"	4000	2500:1	1024 x 768	3000/2000	1.62–2.64	22.4"–303.9"	PureShift Technology, 1.6x Zoom, Manual Zoom, Focus & Lens Shift	2 x 2-Watt Speakers	HDMI, DVI-D w/HDCP, Two VGA-In, VGA-Out, S-Video, Composite Video, Two Stereo Audio-In, RCA Audio-In, Stereo Audio-Out, USB, 12V Trigger	RS-232, RJ45	Built-in support for wired and wireless presentation
<a href="#">TW766W<sup>§</sup></a>	\$1,599	—	12 lb 14.3" x 5" x 11.1"	4000	2500:1	1280 x 800	3000/2000	1.57–2.39	23.2"–295.7"					

<sup>§</sup>Additional authorization may be required to resell these restricted Optoma products. No outbound EDI feed to resellers, no internet resellers.

# TAA COMPLIANT PROJECTORS - Country of Origin: Taiwan



3-Year Express Warranty

Model	MAP	3D	Weight / Dimensions (W x H x D)	LED Lumens	Contrast (Full On/Off)	Native Resolution	LED Life	Throw Ratio	Image Size (Diagonal)	Memory	Speakers /Audio	Inputs/Outputs	Comm and Control	Wired/Wireless Presentation
<a href="#">TL50W-GOV<sup>§</sup></a>	\$729		2.5 lb 8.7" x 1.7" x 6.7"	500	3000:1	1280 x 800	20,000 + hours	1.4	17"-180"	2GB Internal, SD Slot, USB Flash Drive Input	2-Watt Speaker	VGA-In, miniUSB, USB, HDMI, Composite, S-video, Audio-In	—	mini USB WiFi Dongle included
Model	MAP	3D	Weight / Dimensions (WxHxD)	ANSI Lumens	Contrast (Full On/Off)	Native Resolution	Lamp Life (STD/Bright)	Throw Ratio	Image Size (Diagonal)	Projection Lens	Speaker	Inputs/Outputs	Comm and Control	Wired/Wireless Presentation
<a href="#">TX615-GOV<sup>§</sup></a>	\$849		6.4 lb 12.8" x 3.8" x 9.2"	3500	3000:1	1024 x 768	4000/3000	1.95-2.15	27.5"-303"	Manual Zoom and Focus	10-Watt Speakers	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-Out, USB, 12V Trigger	RS-232, RJ45	Wireless via optional VGA dongle
<a href="#">TW615-GOV<sup>§</sup></a>	\$949			3500	3000:1	1280 x 800	4000/3000	1.28-1.54	36.3"-362"					
<a href="#">TX762-GOV<sup>§</sup></a>	\$1,049		6.4 lb 12.8" x 3.8" x 9.2"	4000	3000:1	1024 x 768	3000/2000	1.6-1.92	30"-307"	Manual Zoom and Focus	8-Watt Speaker	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-out, USB, 12V Trigger	RS-232, RJ45	Wireless via optional VGA dongle
<a href="#">TW762-GOV<sup>§</sup></a>	\$1,149			4000	3000:1	1280 x 800	4000/3000	1.28-1.54	36.3"-362"					



TX762-GOV



TW610STi+



TW865-NL



<sup>§</sup>Additional authorization may be required to resell these restricted Optoma products. No outbound EDI feed to resellers, no internet resellers.

# ULTRA SHORT THROW / SHORT THROW PROJECTORS



3-Year Express Warranty

Model	MAP	3D	Weight / Dimensions (WxHxD)	ANSI Lumens	Contrast (Full On/Off)	Native Resolution	Lamp Life (STD/Bright)	Throw Ratio	Image Size (Diagonal)	Projection Lens	Speaker	Inputs/Outputs	Comm and Control	Wired/Wireless Presentation
<b>INTERACTIVE ULTRA SHORT THROW - Includes PointBlank Interactive Pen</b>														
<a href="#">TX665UTiM-3D (with Mount)</a>	\$1,599		16.7 lb 16.8" x 8.27" x 16"	3000	3000:1	1024 x 768	3000/2500	0.38	63"-85"	Manual Focus	2 x 5-Watt Speakers	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, RCA Stereo Audio-In, Stereo Audio-In/Out, Microphone-In, 12V Trigger, Mini-USB for Interactive Pen Output to Computer, Mini-USB for Display, USB Type A (wireless/flash drive)	RS-232, RJ45	Wired and wireless (optional USB dongle)
<a href="#">TW695UTi-3D</a>	\$1,499		16.8 lb 16.8" x 8.27" x 16"	3500	3000:1	1280 x 800	3000/2500	0.3	77"-100"					
<b>INTERACTIVE SHORT THROW - Includes PointBlank Interactive Pen</b>														
<a href="#">TW610STi+</a>	\$999		6.9 lb 12" x 4.5" x 9.6"	3200	3000:1	1280 x 800	4000/3000	0.52	44.6"-222.8"	Manual Focus	2 x 5-Watt Speakers	HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, RCA Stereo Audio-In, Stereo Audio-Out, Microphone-in, mini-USB for Interactive Pen Output to Computer, mini-USB for Display, 12V Trigger, USB Type A (wireless/flash drive)	RS-232, RJ45	Wired and wireless (optional USB dongle)
<b>NON-INTERACTIVE ULTRA SHORT THROW / SHORT THROW</b>														
<a href="#">TX665UST-3D</a>	\$1,299		16.7 lb 16.8" x 8.3" x 16"	3000	3000:1	1024 x 768	3000/2500	0.38	63"-85"	Manual Focus	2 x 5-Watt Speakers	HDMI, Two VGA-In, VGA-Out, S Video, Composite Video, RCA Stereo Audio-In, Stereo Audio-In/Out, Microphone-In, 12V Trigger, Mini-USB for Display, USB Type A (wireless/flash drive)	RS-232, RJ45	Wired and wireless (optional USB dongle)
<a href="#">TW695UT-3D</a>	\$1,299		16.8 lb 16.8" x 8.3" x 16"	3500	3000:1	1280 x 800	3000/2500	0.3	77"-100"	Manual Focus	2 x 5-Watt Speakers	HDMI, Two VGA-In, VGA-Out, S Video, Composite Video, RCA Stereo Audio-In, Stereo Audio-In, Stereo Audio-Out, mini USB, Microphone-In, 12V Trigger	RS-232, RJ45	Wired and wireless (optional USB dongle)
<a href="#">TX610ST</a>	\$849		6.9 lb 12" x 4.5" x 9.6"	3000	3000:1	1024 x 768	4000/3000	0.626	39.3"-196.5"	Manual Focus	2 x 5-Watt Speakers	HDMI, Two VGA-In, VGA-Out, S Video, Composite Video, RCA Stereo Audio-In, Stereo Audio-In, Stereo Audio-Out, Microphone-In, USB	RS-232, RJ45	—
<a href="#">TW610ST</a>	\$899			3100		1280 x 800		0.52	44.6"-222.8"					

# LARGE VENUE PROJECTORS



3-Year Express Warranty

Model	MAP	3D	Weight / Dimensions (WxHxD)	ANSI Lumens	Contrast (Full On/Off)	Native Resolution	Lamp Life (STD/Bright)	Throw Ratio	Image Size (Diagonal)	Projection Lens	Speaker	Inputs/Outputs	Comm and Control
<a href="#">TW775<sup>§</sup></a>	\$2,799		18.1 lb 16.9" x 7.1" x 13.4"	4500	2000:1	1280 x 800	3000/2000	See Lens Chart Below	—	—	2 x 3-Watt Speakers	HDMI, DVI-D w/ HDCP, Two VGA-In, VGA-Out, S-Video, Composite Video, Component Video, Five BNC (RGBHV/YPbPr), Three Stereo Mini Jack Audio-In, Two RCA Stereo Audio-In, Audio-Out, USB, and Two 12V Triggers	RS-232, RJ45
<a href="#">TX785<sup>§</sup></a>	\$2,799		18.1 lb 16.9" x 7.1" x 13.4"	5000	2000:1	1024 x 768	3000/2000	See Lens Chart Below	—	2 x 3-Watt Speakers	RS-232, RJ45		
<a href="#">TW865-NL<sup>§</sup></a>	\$3,999		40.3 lb 21.3" x 7.8" x 16.5"	6000	4000:1	1280 x 800	2000/1500	See Lens Chart Below	—	—	—	HDMI, DVI, Two VGA-In, VGA-Out, S-Video, Composite, Component, RGBHV, BNC, Two Stereo Audio-In, RCA Audio-In, Stereo Audio-Out, USB Type A (wireless/flash drive), Wired Remote In/Out, 12V Trigger	RS-232, RJ45
<a href="#">TH7500-NL<sup>§</sup></a>	\$7,999	—	51.4 lb 21.6" x 9.3" x 17.2"	6000	2000:1	1920 x 1200	2500/2000	See Lens Chart Below	—	—	—	Two HDMI, Two VGA-In, RGBHV BNC, YPbPr Component, S-Video, VGA-Out, 12V Trigger, Composite Video	RS-232, RJ45

# LARGE VENUE LENSES

	Lens Type	Optoma Part Number	Zoom Ratio	Focal Length (f)	Throw Distance	Zoom & Focus Adjustment	Throw Ratio	Projection Image Size (Diagonal)	F Number
TX785 / TW775 Lenses	Short Throw	<a href="#">BX-DL080</a>	Fixed	11.5mm	1.6' ~ 9.8' 0.5 ~ 3m	Manual	0.8	30.0" ~ 184"	2.5
	Standard Throw	<a href="#">BX-DL200</a>	1.25x	22.8 ~ 28.5mm	4.9' ~ 23.0' 1.5 ~ 7m		1.60 ~ 2.00	36.8" ~ 216"	2.46 ~ 2.6
	Long Throw	<a href="#">BX-DL300</a>	1.5x	28.5 ~ 42.75mm	6.6' ~ 65.6' 2 ~ 20m		2.00 ~ 3.00	33.0" ~ 492"	2.5 ~ 3.1
TH7500-NL Lenses	Fixed Short Throw	<a href="#">BX-DLWT1</a>	Fixed	11.73mm	1.65' ~ 27.6' 0.5 ~ 8.4m	Motorized	0.78	30" ~ 500"	2.2
	Short Throw	<a href="#">BX-DLWT2</a>	1.2x	18.1 ~ 21.72mm	2.59' ~ 51.9' 0.79 ~ 15.8m		1.22 ~ 1.47		2.0 ~ 2.3
	Standard Throw	<a href="#">BX-DLST1</a>	1.33x	21.5 ~ 28.77mm	3.07' ~ 68.9' 0.94 ~ 21.0m		1.45 ~ 1.95		2.0 ~ 2.3
	Long Throw	<a href="#">BX-DLTZ1</a>	1.9x	28.6 ~ 54.33mm	4.09' ~ 131.1' 1.25 ~ 40.0m		1.93 ~ 3.71		2.2 ~ 3.0
	Ultra Long Throw	<a href="#">BX-DLTZ2</a>	1.9x	54.06 ~ 102.7mm	7.8' ~ 248.7' 2.38 ~ 75.8m		3.68 ~ 7.04		2.3 ~ 3.16
TW865-NL Lenses	Short Throw	<a href="#">BX-CAA01</a>	1.28x	14.03 ~ 12.95mm	2.8' ~ 44.9' 0.8 ~ 13.7m	Motorized	1.0 ~ 1.28	50" ~ 500"	2.3 ~ 2.57
	Standard Throw	<a href="#">BX-CAA02</a>	1.25x	18.07 ~ 22.59mm	3.6' ~ 57.2' 1.1 ~ 17.4m		1.28 ~ 1.61		2 ~ 2.3
	Long Throw	<a href="#">BX-CAA03</a>	1.9x	22.56 ~ 42.87mm	4.4' ~ 109.2' 1.34 ~ 33.3m		1.6 ~ 3.07		2.3 ~ 3.4



BX-DL080






BX-DLST1





<sup>§</sup>Additional authorization may be required to resell these restricted Optoma products. No outbound EDI feed to resellers, no internet resellers.

## HOME THEATER PROJECTORS\*\*

Model	MAP	3D	Weight / Dimensions (WxHxD)	ANSI Lumens	Contrast (Full On/Off)	Native Resolution	Lamp Life (STD/Bright)	Throw Ratio	Image Size (Diagonal)	Projection Lens	Speaker	Inputs/Outputs
<a href="#">HD20</a>	\$699	—	6.4 lb 12.8" x 3.8" x 9.2"	1700	4000:1	1920 x 1080	4000/3000	1.5–1.8	37.6"–301.1"	Manual Zoom and Focus	—	Two HDMI, VGA-In, Component Video, Composite Video, 12V Trigger
<a href="#">HD66</a>	\$549		5.1 lb 11.3" x 3.9" x 7.6"	2500	4000:1	1280 x 720	4000/3000	1.55–1.7	27.2"–301"	Manual Zoom and Focus	2-Watt Speaker	HDMI, VGA-In, S-Video, Composite Video, Stereo Audio-In, RS-232
<a href="#">HD25-LV</a>	\$1,299		6.4 lb 12.8" x 3.8" x 9.2"	3000	20,000:1	1920 x 1080	6000/3500	1.5–1.8	37.6–301.1	Manual Zoom and Focus	16-Watt Speaker	Two HDMI v1.4a, Two VGA-in, VGA-Out, 3D VESA Port, Composite video, two audio-in, audio-out, RS-232C, USB-B
<a href="#">GT750E</a>	\$599		6.6 lb 12.8" x 3.8" x 9.2"	3000	3000:1	1280 x 800	4000/3000	0.72	32.2"–322.4"	Manual Focus	2 x 5-Watt Speakers	Two HDMI, VGA-In, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-Out, RS-232, VESA 3D Port

## LED PROJECTORS, LAMP-FREE\*\*

Model	MAP	3D	Weight / Dimensions (W x H x D)	LED Lumens	Contrast (Full On/Off)	Native Resolution	LED Life	Throw Ratio	Image Size (Diagonal)	Speakers /Audio	Inputs/Outputs	Digital Input	Memory
<a href="#">PK301+</a>	\$379	N/A	8 oz 4.7" x 1.2" x 2.7"	75	3000:1	854 x 480	20,000 + hours	1.8	5"–120"	0.5-Watt Speaker, Audio-Out	microSD, 24-pin Universal Port for VGA, 2.5mm AV Input (Composite Video and Stereo Audio-in) Micro USB, 3.5mm Audio-out	Mini HDMI	28MB Internal, microSD Slot
<a href="#">PK320</a>	\$399	N/A	8.3 oz 4.7" x 1.2" x 2.7"	100	3000:1	854 x 480	20,000 + hours	1.8	5"–150"	1-Watt Speaker, Audio-Out	microSD, 24-pin Universal Port for VGA, 2.5mm AV Input (Composite Video and Stereo Audio-in), Micro USB, 3.5mm Audio-out	Mini HDMI	2GB Internal, microSD Slot
<a href="#">PT110</a>	\$199	N/A	1.9 lb 7.8" x 3.2" x 7.8"	100	1000:1	854 x 480	20,000 + hours	2.1:1	10"–140"	3-Watt Speaker	HDMI, VGA-in, composite video, audio-in (L/R RCA), DC input	HDMI	—
<a href="#">ML300</a>	\$449		1.4 lb 7.2" x 1.8" x 4.4"	300	3000:1	1280 x 800	20,000 + hours	1.5	17"–160"	2-Watt Speaker, Audio-Out	VGA-in, 2.5mm AV Input Jack (Composite Video and Stereo Audio-in), 3.5mm Audio-out, USB, Micro USB, microSD Slot	Mini HDMI	2GB Internal, microSD Slot, USB Flash Drive Input
<a href="#">ML500</a>	\$599		2.5 lb 8.7" x 1.7" x 6.7"	500	3000:1	1280 x 800	20,000 + hours	1.4	17"–180"	2-Watt Speaker	VGA-In, miniUSB, USB, Composite, S-video, Audio-in	HDMI	2GB Internal, SD Slot, USB Flash Drive Input

\*\*D series, ML series, Home series, and Pico projectors have 1-Year Warranty.



# ECOBRIGHT PROJECTORS, LAMP-FREE



3-Year Express Warranty

Model	MAP	3D	Weight / Dimensions (W x H x D)	LED Lumens	Contrast (Full On/Off)	Native Resolution	LED Life	Throw Ratio	Image Size (Diagonal)	Memory	Speakers /Audio	Inputs/Outputs	Comm and Control	Wired/Wireless Presentation
<a href="#">TL30W<sup>§</sup></a>	\$549		1.4 lb 7.2" x 1.8" x 4.4"	300	3000:1	1280 x 800	20,000 + hours	1.5	17"-160"	2GB Internal, microSD Slot, USB Flash Drive Input	2-Watt Speaker, Audio-Out	Mini HDMI, VGA-in, 2.5mm AV Input Jack (Composite Video and Stereo Audio-in), 3.5mm Audio-out, USB, Micro USB	—	mini USB WiFi Dongle included
<a href="#">TL50W<sup>§</sup></a>	\$649		2.5 lb 8.7" x 1.7" x 6.7"	500	3000:1	1280 x 800	20,000 + hours	1.4	17"-180"	2GB Internal, SD Slot, USB Flash Drive Input	2-Watt Speaker	VGA-In, miniUSB, USB, HDMI, Composite, S-video, Audio-In	—	mini USB WiFi Dongle included
<a href="#">ZX212ST<sup>§</sup></a>	\$1,499		9.4 lb 12.6" x 3.9" x 9.1"	2300	100,000:1	1024 x 768	20,000 + hours	0.626	39.3"-300"	SD slot	2 x 5-Watt Speakers	HDMI, VGA-in, mini-USB for display, USB for wireless, VGA-out, S-Video, Composite Video, Audio-In/Out	RJ45 and mini-din RS-232	Wired and wireless (optional USB dongle)
<a href="#">ZW212ST<sup>§</sup></a>	\$1,599			2500	100,000:1	1280 x 800	20,000 + hours	0.52	44.6"-300"					



TL30W



TL50W



ZX,ZW212ST

## INTERACTIVE ACCESSORIES

Model	MAP	Weight / Dimensions (WxHxD)	Description
<a href="#">Q300 MirrorBoard</a>	\$499	2.4 lb 14.57" x 0.9" x 8.57"	MirrorBoard Interactive Tablet Display, 10.1" LCD Display, 500:1 Contrast, Rechargeable with 2.5 Hours Use, Battery-Free Pen Design, WiFi Interaction with Computer, 3-Year Warranty
<a href="#">DC300i Document Camera</a>	\$349	3.97 lb 6.7" x 10.5" x 14" (folded) 6.7" x 16.5" x 17.5" (setup)	Portable Gooseneck Document Camera, SXGA, 2 Megapixels, 9x Optical Zoom, 12x Digital Zoom, 5-Year Warranty



Q300 MirrorBoard



DC300i

<sup>§</sup>Additional authorization may be required to resell these restricted Optoma products. No outbound EDI feed to resellers, no internet resellers.



## PROJECTOR ACCESSORIES

PROJECTOR PART NUMBER	LAMP	REMOTE	CASE	MOUNT
TX665UTiM-3D, TX665UST-3D, TW695UTi-3D, TW695UT-3D	BL-FU280C	BR-5035N	N/A	BM-3002N
TX610ST, TW610ST	BL-FP230F	BR-3054N	N/A	BM-3001N
TW610STi+	BL-FP230F	BR-5035N	N/A	BM-3001N
TX330, TW330	BL-FP165A	BR-5021L	BK-4022	N/A, 3rd party recommended mount: Peerless PRS35
TX7156, TW1692	BL-FS220B	BR-5028L	BK-4021	BM-5001U
TS551, TX551	BL-FP180F	BR-3057L	BK-4018	BM-5001U
DX339	BL-FU190A	BR-5041L	N/A	BM-5001U
TW615-3D, TH1020	BL-FP230D	BR-5030L	BK-4028	BM-5001U
TX631-3D, TW631-3D	BL-FP240A	BR-3057L	N/A	BM-5001U
TX635-3D, TW635-3D	BL-FP240B	BR-5039L	N/A	BM-5001U
TX762, TW762	BL-FP280D	BR-5030L	BK-4028	BM-5001U
TX779P-3D, TH1060P	BL-FS300C	BR-5033L	N/A	BM-5001U
TX765W, TW766W	BL-FU280B	BR-5029L	N/A	BM-5001U
HD66	BL-FU185A	BR-3048N	N/A	BM-5001U
HD20	BL-FP230D	BR-3042B	BK-4028	BM-5001U
GT750E	BL-FP230H	BR-3059N	BK-4028	BM-5001U
TX785, TW775	BL-FP330B	BR-5032L	N/A	BM-5001U
TH7500-NL	BL-FP330C	BR-3055B	N/A	BM-9002N
TW865-NL	BL-FU400A	BR-7001N	N/A	TBD
ZX212ST, ZW212ST	N/A	BR-5038L	BK-4028	BM-3004U
PK301+	N/A	BR-PK3AN	BK-PK33S	BM-PK30TA
PK320	N/A	BR-PK32N	BK-PK33S	BM-PK30TA
ML300, TL30W	N/A	BR-ML30N	BK-ML30S	N/A
ML500, TL50W	N/A	BR-ML50N	BK-ML50S	N/A



Contact Information:

All specifications and pricing subject to change without notice.

3D content can be viewed with active shutter LCD glasses when the projector is connected to a computer with a compatible 3D graphics card.

Lamp life is dependent on many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

[www.OptomaUSA.com](http://www.OptomaUSA.com)

Copyright © 2013 Optoma Technology, Inc.