

EP719 – Multimedia Projector

Brilliant Performance, Brilliant Price

The Optoma EP719 is an award-winning, versatile multimedia projector. From the boardroom to the classroom, the EP719 features 2200 lumens, sharp resolution and great contrast for a variety of environments. Designed for today's demanding multimedia needs, this sturdy DLP® digital projector lets your presentations shine.

Features

- Native XGA (1024 x 768) resolution displays sharp images
- 2200 lumens for bright pictures in a wide range of environments
- 2500:1 contrast ratio for superior image quality and crisp details
- SXGA+ (1400 x 1050) resolution and HDTV compatibility
- Advanced connectivity including DVI w/HDCP, component, composite and s-video inputs
- Lightweight at only 4.4 pounds

Specifications

Brightness

2200 ANSI Lumens

Display Technology

Single 0.55" DDR DLP® Technology by Texas Instruments

Resolution

XGA (1024 x 768)

Maximum Resolution

PC: SXGA+ (1400 x 1050)

Brightness (Typical)

2000 Lumens

Contrast Ratio

2500:1 (Full On/Full Off)

Lamp Life and Type

2000/3000 Hours (STD/ECO)
200W UHP

Throw Ratio

1.93 - 2.13:1 (Distance/Width)

Image Size (Diagonal)

24.6" to 300" (0.6 to 7.62 m)

Projection Distance

3.9' to 32.8' (1.2 to 10 m)

Noise Level

32dB/28dB (STD/ECO)

Remote Control

IR Remote

Audio

One 2-Watt Speaker

Computer Compatibility

XGA, SVGA, VGA, SXGA +, VESA, PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)

User Controls

Complete On Screen Menu Adjustments in 11 Languages

Aspect Ratio

4:3 Native, 16:9 Compatible

Projection Lens

F=2.7-3.0, f=21.83-23.81 mm, 1.2:1 Manual Zoom and Focus

Keystone Correction

± 15° Vertical

Horizontal Scan Rate

15 to 100 kHz

Vertical Refresh Rate

56 to 85 Hz

Displayable Colors

16.7 Million

I/O Connectors

DVI w/HDCP, VGA-In, S-Video, Composite Video, Audio Mini-Jack, RS-232, VGA-Out

Security

One Kensington® Lock Port

Uniformity

85%



Projection Method

Front, Rear, Ceiling Mount, Table Top

Weight

4.4 lbs (2.0 kg)

Dimensions (W x H x D)

9" x 3.7" x 8.26"
(230 x 95 x 210 mm)

Power Supply

AC Input 100-240V, Auto-Switching

Power Consumption

265 Watts (Max), <15 Watts (Standby)

Operating Temperature

41 - 95°F (5 - 35°C) (80% Humidity), Adjustable Fan Speed for High Altitude Application

Standard Accessories

AC Power Cord, VGA to VGA Cable, Composite Video Cable, Lens Cap, Remote Control, Batteries for Remote, Quick Start Guide, Warranty Card and User's Manual

Optional Accessories

Ceiling Mount, GrayWolfII™ Series Screens, VGA to Component Cable, S-Video Cable, Audio-Out Adapter and Gold Service Warranty

Warranty

1 Year Limited Parts and Labor, 90 Days on Lamp

UPC

796435 11 607 1